

Series CS-2015

Advanced Technology Synthetic Compressor Lubricant

Series CS-2015 utilizes the latest high-performance, full-synthetic base stocks and additives. These advanced lubricants offer an exceptional level of protection against wear, rust and corrosion, as well as outstanding resistance against oxidation and thermal breakdown.

Series CS-2015 is designed to provide 8,000+ hours of service.

ATTRIBUTES

- Very long fluid life
- Excellent resistance against water contamination
- Enhanced energy savings
- Very high flash point
- Excellent protection against wear, rust and corrosion
- Reduced maintenance costs and downtime
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	CS-2015-32	CS-2015-46	CS-2015-68	CS-2015-100
Viscosity cSt @ 40°C	34	49	69.8	106
Viscosity cSt @ 100°C	6.1	7.9	10.2	11.8
Flash Point °F	440	450	498	501
Auto-Ignition Point °F	735	785	790	800
Pour Point °F	-64	-61	-57	-55
Four Ball, 40 Kg, 1200 RPM, 167°F, 1 hr, Scar Dia mm	.40	.40	.40	.40
Four Ball Weld Point, Kg	100	100	110	150
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/38/2
Foam Sequence I, II, III	Nil	Nil	Nil	Nil